


# CTP-VD (Current Transfer Prep-Von Duprin®) Pin & Barrel Hinge Electric Prep



**PREP:** SELECT pin & barrel continuous hinges can be prepared for Von Duprin power transfer unit.

**LOCATION:** Standard locations from top of hinge to centerline of CTP-VD are as follows:

- 79" hinge = 39-3/8"
- 83" hinge = 41-9/16"
- 85" hinge = 42-1/2"
- 95" hinge = 47-1/2"

For custom locations, specify centerline dimension from top of hinge. Hinge is installed flush with the top of the door.

For CTP-VD prep on a Concealed Pin & Barrel hinge, refer to the templates in the Concealed Pin & Barrel Hinge section. For CTP-VD prep on a Half Surface or Half Mortise Pin & Barrel hinge, please consult the factory. The Concealed Pin & Barrel hinge templates are also available online at [www.select-hinges.com/app](http://www.select-hinges.com/app).

**HANDING:** Specify the handing of each door requiring the CTP-VD.

**ORDER:** Use suffix "CTP-VD," plus the location and handing.

*Example: SL300 83" SS, CTP-VD 39-3/8" from top of hinge to centerline, LH.*

**AVAILABILITY:** Available on pin & barrel hinge models SL200, SL300, SL303, SL305, SL306, SL315 and SL3500.

**LEAD TIME:** Contact your SELECT representative.

**WARRANTY:** 5 years on electrical components.

**IMPORTANT:** SELECT Products Limited does not recommend preparing door and frame for CTP-VD before receipt of hinge. If door and frame must be prepared before receipt of hinge, contact factory for special template.

CTP-VD Prep