



**PREP:** SELECT pin & barrel continuous hinges can be prepared for concealed electric through-wires to provide continuous current. 28 gauge through-wires with ElectroLYNX™ connectors available in sets of 4 (EL-4), 8 (EL-8) or 12 (EL-12).

**LOCATION:** Specify the dimension from the top of the hinge to the EL centerline. Hinge is installed flush with the top of the door.

*Refer to the templates in the Concealed Pin & Barrel Hinge section to choose from available EL locations. These templates are also available online at [www.select-hinges.com/app](http://www.select-hinges.com/app).*

**HANDING:** Specify the handing of each door requiring the EL.

**ORDER:** Use suffix “EL-4”, “EL-8” or “EL-12” (depending on number of wires required). Specify location and handing. Only one location is required, whether 4, 8 or 12 wires.

*Example: SL300 83" SS, EL-4 41-9/16" from top of hinge to centerline, LH.*

**AVAILABILITY:** Available on pin & barrel hinge models SL200, SL300, SL305, SL315 and SL3500. **NOT AVAILABLE** on raised barrel applications.

**LEAD TIME:** Contact your SELECT representative.

**WARRANTY:** 5 years on electrical components.

**IMPORTANT:** SELECT Products Limited does not recommend preparing door and frame for EL before receipt of hinge. If door and frame must be prepared before receipt of hinge, contact factory for special template.